

22BL

无刷直流电机
BRUSHLESS DC MOTOR

详细说明 General Specifications

绕线接法	Winding Type	Star
霍尔角度	Hall effect angle	120° Electrical angle
绝缘等级	Insulation Class	B
环境温度	Ambient Temperature	-20°C~+50°C
绝缘电阻	Insulation Resistance	100MΩ Min.500 VDC
绝缘强度	Dielectric Strength	600VAC 1 minute
最大径向负荷	Max Radial Force	10N (10mm from front flange)
最大轴向负荷	Max Axial Force	2N

技术数据 Technical Specifications

电机型号 Model	极数 No. of Poles	相数 No. of Phase	额定电压 Rated Voltage	额定转矩 Rated Torque	额定转速 Rated Speed	额定电流 Rated Current	输出功率 Output Power	峰值扭矩 Peak Torque	峰值电流 Peak Current	力矩常数 Torque Constant	反电势常数 Back EMF Constant	机身高度 Motor Height L	重量 Motor Weight
			(VDC)	(N.M)	(RPM)	(Amps)	(Watts)	(N.M)	(Amps)	(N.M/Amps)	(V/kRPM)	(mm)	(kg)
22BL201-001	8	3	24	0.02	4800	0.6	8.0	0.06	1.8	0.033	3.5	68	0.11

*以上仅为代表产品, 派生产品可按客户需求定制。
*Products can be customized by special request.

*该产品可适配22减速箱。
*Products can match gearbox 22.

接线图 Wiring Diagram

外型图 Mechanical Dimension

ELECTRICAL CONNECTION TABLE/接线表			
FUNCTION/功能	COLOR/颜色		
TP	ORANGE	橙	UL1061 26AWG
GND	BLACK	黑	UL1332 28AWG
PHASE A	BROWN	棕	
PHASE B	WHITE	白	
PHASE C	PURPLE	紫	
+5V	RED	红	
HALL A	YELLOW	黄	
HALL B	GREEN	绿	
HALL C	BLUE	蓝	

